

Type B - T8 Glass LED Tube Shatterproof

Item No.		
Size	T8 4ft	T8 4ft
Power	18W	24W
Efficiency	125Lm/W	125Lm/W
Lumen	2200Lm	3000Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base	G13	G13
Beam Angle	270° frosted	270° frosted



- 1. Shatterproof, PET safty-coating.
- 2. Single & Dual end power, easy installation, reduce stock.
- 3. Ballast Bypass, instant start, no flickering, energy saving.



Type B- T8 Glass LED Tube Clear Lens

Item No.		
Size	T8 4ft	T8 4ft
Power	18W	24W
Efficiency	125Lm/W	125Lm/W
Lumen	3000Lm	3000Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base	G13	G13
Beam Angle	320°clear	320°clear



- 1. Clear lens, more bright light output.
- 2. Single & Dual end power, easy installation, reduce stock.
- 3. Ballast Bypass, instant start, no flickering, energy saving.



Type B- T8 Alu+PC LED Tube

Item No.		
Size	T8 4ft	T8 4ft
Power	18W	24W
Efficiency	125Lm/W	125Lm/W
Lumen	1500Lm	2200Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base	G13	G13
Beam Angle	120°frosted / clear	120°frosted / clear

- 1. Half Alu + Half PC housing, good heat dissipation, strong stucture, safe for transportation.
- 2. Single & Dual end power, easy installation, reduce stock.
- 3. Ballast Bypass, instant start, no flickering, energy saving.



Type B- T8 Alu+PC LED Tube

Item No.					
Size	T8 2ft	T8 3ft	T8 4ft	T8 5ft	T8 6ft
Power	15W	20W	20W	35W	40W
Efficiency	125Lm/W	125Lm/W	125Lm/W	125Lm/W	125Lm/W
Lumen	1800Lm	2500Lm	2500Lm	4300Lm	5000Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K	3K/4K/5K/6K	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra	80Ra	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz	100-277V 50/60Hz	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9	0.9	0.9	0.9
Base	G13	G13	G13	G13	G13
Beam Angle	120°frosted / clear	120°frosted / clear	120°frosted / clear	120°frosted / clear	120°frosted / clear



- 1. Half Alu + Half PC housing, good heat dissipation, strong stucture, safe for transportation.
- 2. High Power, satisfy high bright requirement.
- 3. Single & Dual end power, easy installation, reduce stock.
- 4. Ballast Bypass, instant start, no flickering, energy saving.



8ft T8 Alu+PC LED Tube

Item No.		
Size	T8 8ft	T8 8ft
Power	40W	50W
Efficiency	125Lm/W	125Lm/W
Lumen	5000Lm	6200Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base	FA8	FA8
Beam Angle	120°frosted / clear	120°frosted / clear



- 1. Half Alu + Half PC housing, good heat dissipation, strong stucture, safe for transportation.
- 2. Single & Dual end power, easy installation, reduce stock.
- 3. Ballast Bypass, instant start, no flickering, energy saving.



Type A+B- T8 Glass LED Tube Shatterproof

Item No.		
Size	T8 4ft	T8 4ft
Power	18W	24W
Efficiency	125Lm/W	125Lm/W
Lumen	2200Lm	2200Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base	G13	G13
Beam Angle	270° frosted	270° frosted



end ballast bypass, easy installation.



Type A+B-T8 Glass LED Tub Clear Lens

Item No.		
Size	T8 4ft	T8 4ft
Power	18W	24W
Efficiency	125Lm/W	125Lm/W
Lumen	3000Lm	3000Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base	G13	G13
Beam Angle	320°clear	320°clear




bypass, easy installation.



Type A+B-T8 Alu+PC LED Tube

Item No.		
Size	T8 4ft	T8 4ft
Power	12W	18W
Efficiency	125Lm/W	125Lm/W
Lumen	1500Lm	2200Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base	G13	G13
Beam Angle	120°frosted / clear	120°frosted / clear




- 1. Half Alu + Half PC housing, good heat dissipation, strong stucture, safe for transportation.
- 2. Ballast compatible, Plug & Play direct, Single & Dual end ballast bypass, easy installation.
- 3. Easy for stocking, reduce stock.



LED Batten

Item No.		
Size	T8 4ft	T8 4ft
Power	30W	64W
Efficiency	120Lm/W	120Lm/W
Lumen	3600Lm	7600Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base		
Beam Angle	120°frosted / clear	120°frosted / clear



- 1.
- 2.
- 3.



LED Batten




- 1.
- 2.
- 3.
- 4.



Item No.						
Size	T8 2ft	T8 3ft	T8 4ft	T8 5ft	T8 6ft	T8 8ft
Power	18W	20W	36W	40W	48W	72W
Efficiency	125Lm/W	120Lm/W	120Lm/W	120Lm/W	120Lm/W	120Lm/W
Lumen	2200Lm	2400Lm	4300Lm	4800Lm	5700Lm	9600Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K	3K/4K/5K/6K	3K/4K/5K/6K	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra	80Ra	80Ra	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz	100-277V 50/60Hz	100-277V 50/60Hz	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9	0.9	0.9	0.9	0.9
Base						
Beam Angle	120°frosted / clear	120°frosted / clear	120°frosted / clear	120°frosted / clear	120°frosted / clear	120°frosted / clear

Ip55 LED Batten

Item No.		
Size	T8 4ft	T8 8ft
Power	40W	72W
Efficiency	120Lm/W	120Lm/W
Lumen	4800Lm	9600Lm
CCT	3K/4K/5K/6K	3K/4K/5K/6K
CRI	80Ra	80Ra
Voltage	100-277V 50/60Hz	100-277V 50/60Hz
PF	0.9	0.9
Base		
Beam Angle	120°frosted / clear	120°frosted / clear



- 1.
- 2.
- 3.

